Volume Estimation -Release History

Approach and Results

• Review inventory records to determine volume(s) and date(s) of release(s)

Advantages

 Relatively simple and statistically accurate if accurate historical data are available

Disadvantaaes

 Data rarely accurate given numerous potential error sources (e.g., measurement technique, volume changes due to temperature)

EPA Office of Underground Storage Tanks

Effective Free Product Recovery

Volume Estimation -TPH Concentration in Soil Samples

Approach and Results

Convert TPH concentrations in soil samples to saturations and integrate these values over the area of contamination

Advantages

Data are relatively easy to collect; several methods are available for data integration

Disadvantages

Calculations required are relatively complicated; requires a lot of data to reduce uncertainty associated with calculated volume; results may differ among various methods for data integration; TPH analysis may not be representative of actual petroleum hydrocarbon saturations

BEPA Office of Underground Storage Tanks

Effective Free Product Recovery

Convert TPH Results to Saturation

$$S_o = TPH \times \frac{(1 - \phi)\rho_{gr} \times 10^{-6} \frac{kg}{mg}}{\phi \rho_o}$$

where:

total hydrocarbon saturation (dimensionless)

total petroleum hydrocarbon concentration in mg/kg

grain density (typically 2.65 g/cm³)

porosity (dimensionless)

density of the hydrocarbon, liquid (g/cm3)



EPA Office of Underground Storage Tanks

Effective Free Product Recovery

Convert TPH Results to Saturation

Free hydrocarbon saturation is:

$$S_{of} = S_O - S_r$$

Where:

 S_{of} = free hydrocarbon saturation.

 $S_r = residual$ hydrocarbon saturation.

EPA Office of Underground Storage Tanks

HSI GeoTrans, inc.